

DUAL LEVEL CHARGE CORD PRODUCT DATA SHEET



DESCRIPTION	SPECIFICATION
Model	EVSE-CSS56600012-1003
Input Voltage (AC)	85-255 V
Output Power (amps)	12A continuous with NEMA 5-15 32A continuous with NEMA 14-50
Frequency (Hz)	50 / 60
Number of Phases	1
Circuit Breaker Rating	15A with NEMA 5-15 40A / 50A with NEMA 14-50
Plug Type	Detachable, NEMA 5-15P and NEMA 14-50P included
Charge Coupler	SAE J1772 compliant
Cable Length	25ft assembled
Weight	Main Assembly: 7lb (3.17kg) NEMA 5-15P: 0.88lb (0.4kg) NEMA 14-50P: 1.3lb (0.6kg)
Operating Temp	-22°F to +122°F (-30°C to +50°C)
Ventilation	Not Required
Enclosure Type	NEMA 4X
Indoor/Outdoor Rating	IEC 60529 IP66 Rated, Suitable for Outdoor Usage
Certification	UL, cUL, NOM, Energy Star



For use with electric vehicles. Have a qualified electrician confirm an intended electrical outlet/circuit can withstand the heavy-duty continuous load of EV charging before use.

CAUTION

To reduce the risk of electric shock, connect only to properly grounded outlets.
Do not use this product if there is any damage to the unit.
Risk of electric shock. Do not remove cover or attempt to open the enclosure. No user serviceable parts inside. Refer servicing to qualified service personnel.

WARNING

To avoid a risk of fire or electric shock, do not use this device with an extension cord.
This device is intended only for charging vehicles not requiring ventilation during charging.
Refer to additional safety warnings found in product insert and vehicle owner's manual.